



A26015 KAYAK MOUNT KIT

Owner's Manual



OVERVIEW

The kayak mount kit is a great way to haul a kayak on Truckify rack systems. The kayak mounts are intended to be mounted on our Full Rack Kit, which is a rack that is higher than the height of the truck cab, allowing longer things, like kayaks, to be mounted on the rack. Other things like canoes, paddleboards, and surfboards, can also be mounted to these kayak mounts. Please read the instructions carefully, and be sure to follow each step as shown, to ensure a proper and safe installation.



STEP 1

Before installation, make sure that the mount brackets are tightly bolted to each kayak mount.



STEP 2

Loosely assemble (4) Wing Bolts and T Nuts in both of the mount brackets.

STEP 3

Slide kayak mounts on rack crossbars to your desired location, making sure the kayak mounts are in line with each other. Make sure the T Nuts are sliding into the T slot of the rack. The kayak is most secure when the mounts are farther apart, giving you more protection against a kayak falling off of the rack. Please adjust the rack crossbars to have a minimum width of 4 feet (48 Inches) apart.



STEP 4

Tighten all (4) Wing Bolts by hand.



STEP 5

Lift your kayak onto the mounts, the kayak should be centered in the mounts. Then, walk around and make sure you have a proper horizontal angle on both of the upright arms. To adjust, open the lever and move to your desired angle. A good angle will fit the kayak nicely with minimal gaps. To lock the arms in place, simply close the lever, and the teeth in the arm will lock together.

STEP 6

To secure the kayak, use the provided mounting straps to tie it down. First, take the loose end of the strap and feed it in between the kayak and the mount, on the backside, as pictured.



STEP 7

Take the loose end of the strap and place it over the top of the kayak to the other side. This forms a loop around the kayak mount upright.



STEP 8

Move to the other side of the kayak, and feed the jaw end of the strap in between the mount and the kayak as pictured.



STEP 9

Take the loose end of the strap and feed it through the jaws as pictured.



STEP 10

Sinch the strap tightly. Pull on the loose end while holding the jaws open. Once it is tight, keep tension on the loose end as you release the jaws, this will lock the strap in place.



STEP 11

Tie up the loose end using the velcro near the jaws.



STEP 12

If your Wing Bolts are stuck after tightening them by hand, you can use a screwdriver or a crescent wrench to loosen the bolts.



Warning and Safety Instructions

- No more than 3 non motorized watercrafts should be mounted at one time on any Truckify rack systems.
- The kayak mount kit is intended only to be mounted at an over the cab height, because the length of kayaks or canoes exceed most truck bed lengths.
- Driving with loose bolts, fasteners, or mounting straps can lead to serious injury or death, as well as damage to equipment.
- Failure to follow the instructions can lead to serious injury or damage to equipment.
- The mounting straps should be at a minimum width of 4 feet (48 Inches) apart.
- This product is intended only for use with kayaks, paddleboards, canoes, or other non motorized watercrafts that are similar to these.
- Hauling a watercraft on these mounts could cause height clearance issues, causing injury or damage to equipment. Always pay attention to the height of your load, especially in parking garages, offroad, and other places where height is low.

Replacement/new parts can be found on our website: **Truckify.com**

- A16026 Wing Bolt T Nut Kit
- A26015 Kayak Mount Kit

Returns

All returned products must have prior authorization from Truckify before they are shipped back to our facility. Returned products without pre-authorization are not eligible for credit. There will be a 20% restock fee on returned items. Products must be returned within 60 days of the date of sale to be eligible for credit. To request a return, go to our website, Truckify.com, under returns, to submit a return.

Warranty

This product comes with a limited one year warranty. Products manufactured by Truckify are warranted to be free of defects due to faulty material or workmanship for 12 months from the date of purchase. Normal wear and tear is not considered a defect in material or workmanship. Liability under this warranty is limited to the replacement of the defective part provided that the following conditions are met:

- Truckify is promptly notified in writing of such defect immediately upon discovery, and the defective product is returned for inspection
- The defect is not due, without limitation, to faulty installation, misalignment of the product, vibration, pressure pulsations, ordinary wear and tear, corrosion, ultraviolet degradation, operation outside the product specified limits and using the product for uses other than its intended use



877-885-4994

Truckify.com

support@truckify.com

9479 County Road E,
Arpin, WI 54410